

# Film Capacitors

## EF9-X2 MKP Metallized Polypropylene Film Capacitors

**ELECSOUND®**


Elecsound X2-MKP are non-inductively wound with metallized polypropylene film as the dielectric/electrode with copper-clad steel leads and encapsulated in a plastic case sealed with flame retardant epoxy resin (UL94V-0).

### Features:

- Compact size
- Box type provides the identical dimensions
- Excellent flame retardant abilities
- Very low loss at high frequency, excellent temperature characteristics, suitable for high current
- High insulation resistance, excellent self-healing property and high reliability
- With standing 2.5KV impulse voltage
- Widely used in interference suppression circuits

### Technical Specifications:

- Reference Standard: GB/T 14472 (IEC60384-14)
- Climatic Category: 40/100/21
- Rated Voltage: 250/275VAC
- Capacitance Range: 0.0022 ~ 4.7 $\mu$ F
- Capacitance Tolerance:  $\pm 10\%$  (K);  $\pm 20\%$  (M)
- Voltage Proof: 2100VDC (2S)
- Dissipation Factor:  $\leq 0.001$  (20 $^{\circ}$ C, 10 KHz)
- Insulation Resistance:
  - $\geq 15000M\Omega$  @ Cr  $\leq 0.33\mu$ F (20 $^{\circ}$ C, 1 min)
  - $\geq 5000s$  @ Cr  $> 0.33\mu$ F (20 $^{\circ}$ C, 1 min)



### Dimensions: (mm)

| $\mu$ F | 275VAC |      |     |    |     | $\mu$ F | 275VAC |      |     |      |     |
|---------|--------|------|-----|----|-----|---------|--------|------|-----|------|-----|
|         | W      | H    | T   | P  | D   |         | W      | H    | T   | P    | D   |
| 0.0022  | 13     | 9    | 4   | 10 | 0.6 | 0.12    | 18     | 13   | 6.5 | 15   | 0.8 |
| 0.0027  | 13     | 9    | 4   | 10 | 0.6 | 0.15    | 18     | 13   | 7.5 | 15   | 0.8 |
| 0.0033  | 13     | 9    | 4   | 10 | 0.6 | 0.18    | 18     | 14.5 | 8.5 | 15   | 0.8 |
| 0.0039  | 13     | 9    | 4   | 10 | 0.6 | 0.22    | 18     | 14.5 | 8.5 | 15   | 0.8 |
| 0.0047  | 13     | 11   | 5   | 10 | 0.6 | 0.27    | 26.5   | 16.5 | 8.5 | 22.5 | 0.8 |
| 0.0056  | 13     | 11   | 5   | 10 | 0.6 | 0.33    | 26.5   | 16.5 | 7   | 22.5 | 0.8 |
| 0.0068  | 13     | 11   | 5   | 10 | 0.6 | 0.39    | 26.5   | 20   | 10  | 22.5 | 0.8 |
| 0.0082  | 13     | 11   | 5   | 10 | 0.6 | 0.47    | 26.5   | 20   | 10  | 22.5 | 0.8 |
| 0.01    | 13     | 11   | 5   | 10 | 0.6 | 0.56    | 32     | 20   | 11  | 27.5 | 0.8 |
| 0.012   | 13     | 11   | 5   | 10 | 0.6 | 0.68    | 32     | 20   | 11  | 27.5 | 0.8 |
| 0.015   | 13     | 11   | 5   | 10 | 0.6 | 0.82    | 32     | 22   | 13  | 27.5 | 0.8 |
| 0.018   | 13     | 11   | 5   | 10 | 0.6 | 1       | 32     | 22   | 13  | 27.5 | 0.8 |
| 0.022   | 13     | 11   | 5   | 10 | 0.6 | 1.5     | 37     | 26.5 | 17  | 31.5 | 0.8 |
| 0.027   | 13     | 11   | 5   | 10 | 0.6 | 1.8     | 37     | 29   | 19  | 31.5 | 0.8 |
| 0.033   | 13     | 11   | 5   | 10 | 0.6 | 2       | 38     | 28   | 18  | 31.5 | 0.8 |
| 0.039   | 13     | 12   | 6   | 10 | 0.6 | 2.2     | 38     | 29   | 19  | 31.5 | 0.8 |
| 0.047   | 18     | 11   | 6   | 15 | 0.8 | 2.5     | 38     | 30   | 20  | 31.5 | 0.8 |
| 0.056   | 18     | 12   | 6   | 15 | 0.8 | 3       | 38     | 30   | 20  | 31.5 | 0.8 |
| 0.068   | 18     | 11   | 5   | 15 | 0.8 | 3.3     | 38     | 31.5 | 22  | 31.5 | 0.8 |
| 0.082   | 18     | 11.5 | 5.5 | 15 | 0.8 | 4       | 48     | 30   | 30  | 41.5 | 1.0 |
| 0.1     | 18     | 12   | 6   | 15 | 0.8 | 4.7     | 48     | 30   | 30  | 41.5 | 1.0 |

Note: Capacitors of special specifications are made according to customer's need.

## Elecsound Technology Company Limited

TEL: 0086-755-82908842 FAX: 0086-755-83045964

Website: [www.elecsound.com](http://www.elecsound.com)

Email: [sales@elecsound.com](mailto:sales@elecsound.com)